

## Tubes sans soudure iso-gaz-métrique

Exécution suivant EN 10216-5 / NFA 49117 / ASTM A 269 - 14306 (304 L) / 14541 (321) / 14404 (316 L) / 14571 (316 TI) / 14845 (310 S) - 14539 (904 L)  
Longueurs courantes 5000 à 7000 mm environ.

| DÉSIGNATION | POIDS/ML |
|-------------|----------|
| 6x1         | 0,13     |
| 6x1.5       | 0,17     |
| 8x1         | 0,18     |
| 8x1,5       | 0,24     |
| 8x2         | 0,30     |
| 10x1        | 0,23     |
| 10x1.5      | 0,32     |
| 10x2        | 0,41     |
| 10.2x2      | 0,41     |
| 12x1        | 0,28     |
| 12x1.5      | 0,39     |
| 12x2        | 0,50     |
| 13.5x1.6    | 0,48     |
| 13.5x2.3    | 0,65     |
| 14x1        | 0,33     |
| 14x2        | 0,60     |
| 15x1        | 0,35     |
| 15x1,5      | 0,51     |
| 15x2        | 0,65     |
| 16x1        | 0,38     |
| 16x1,5      | 0,55     |
| 16x2        | 0,70     |
| 17.2x1.6    | 0,63     |
| 17.2x2.3    | 0,86     |
| 18x1        | 0,43     |

| DÉSIGNATION | POIDS/ML |
|-------------|----------|
| 18x1,5      | 0,62     |
| 18x2        | 0,80     |
| 20x1        | 0,48     |
| 20x1.5      | 0,70     |
| 20x2        | 0,90     |
| 21.3x1.6    | 0,79     |
| 21.3x2      | 0,97     |
| 21.3x2.6    | 1,22     |
| 22x1        | 0,53     |
| 22x1,5      | 0,77     |
| 22x2        | 1,00     |
| 23x1,5      | 0,81     |
| 25x1        | 0,60     |
| 25x1,5      | 0,88     |
| 25x2        | 1,15     |
| 25x2,5      | 1,41     |
| 25x3        | 1,65     |
| 26.9x1.6    | 1,01     |
| 26.9x2      | 1,25     |
| 26.9x2.6    | 1,58     |
| 28x1,5      | 1,00     |
| 28x2        | 1,30     |
| 30x2        | 1,40     |
| 30x3        | 2,03     |
| 33.7x1.6    | 1,29     |

| DÉSIGNATION | POIDS/ML |
|-------------|----------|
| 33.7x2      | 1,59     |
| 33.7x2,6    | 2,02     |
| 33.7x3.2    | 2,44     |
| 38x1,5      | 1,37     |
| 38x2        | 1,80     |
| 42.4x1.6    | 1,64     |
| 42.4x2      | 2,02     |
| 42.4x3.2    | 3,14     |
| 48.3x1.6    | 1,87     |
| 48.3x2      | 2,32     |
| 48.3x3.2    | 3,61     |
| 60.3x2      | 2,92     |
| 60.3x3.6    | 5,11     |
| 76.1x2      | 3,71     |
| 76.1x3.6    | 6,54     |
| 88.9x2      | 4,35     |
| 88.9x4      | 8,50     |
| 101.6x4     | 9,78     |
| 108x4       | 10,40    |
| 114.3x4.5   | 12,37    |
| 133x4       | 12,92    |
| 159x4.5     | 17,41    |

## Tubes "pétrole" sans soudure ou soudés

Exécution suivant EN 10216-5 / NFA 49117 / ASTM A 312 - 1.4306 (304 L) / 1.4541 (321) / 1.4404 (316 L) / 1.4571 (316 Ti) / 1.4845 (310 S) - 1.4539 (904 L)

Longueurs courantes 6000 environ en soudé et 5000 à 7000 mm en sans soudure.

| DÉSIGNATION   | ASTM ET MM | POIDS |
|---------------|------------|-------|
| 1/4 SCH 40s   | 13,7X2,24  | 0,64  |
| 1/4 SCH 80s   | 13.7x3.02  | 0,81  |
| 3/8 SCH 40 s  | 17,1X2,31  | 0,85  |
| 3/8 SCH 80s   | 17,1x3.2   | 1,11  |
| 1/2 SCH 10S   | 21.34x2.11 | 1,02  |
| 1/2 SCH 40S   | 21.34x2.77 | 1,29  |
| 1/2 SCH 80S   | 21.3x3.73  | 1,64  |
| 3/4 SCH 10S   | 26.67x2.11 | 1,30  |
| 3/4 SCH 40S   | 26.67x2.77 | 1,71  |
| 3/4 SCH 80S   | 36.7x3.91  | 2,23  |
| 1 SCH 10S     | 33.4x2.77  | 2,13  |
| 1 SCH 40S     | 33.4x3.38  | 2,54  |
| 1 SCH 80S     | 33.4x4.55  | 3,29  |
| 1 1/4 SCH 10S | 42.16x2.77 | 2,73  |
| 1 1/4 SCH 40S | 42.16x3.56 | 3,44  |
| 1 1/4 SCH 80S | 42.4x4.85  | 4,54  |
| 1 1/2 SCH 10S | 48.3x2.77  | 3,16  |
| 1 1/2 SCH 40S | 48.3x3.68  | 4,11  |
| 1 1/2 SCH 80S | 48.3x5.08  | 5,50  |
| 2 SCH 10S     | 60.33x2.77 | 3,99  |
| 2 SCH 40S     | 60.33x3.91 | 5,52  |
| 2 SCH 80S     | 60.33x5.54 | 7,60  |
| 2 1/2 SCH 10S | 73.02X3.05 | 5,25  |
| 2 1/2 SCH 40S | 73.02x5.16 | 8,77  |

| DÉSIGNATION   | ASTM ET MM  | POIDS |
|---------------|-------------|-------|
| 2 1/2 SCH 80S | 73,02X7,01  | 11,40 |
| 3 SCH 10S     | 88.9x3.05   | 6,59  |
| 3 SCH 40S     | 88.9x5.49   | 11,47 |
| 3 SCH 80S     | 88.9x7.62   | 15,51 |
| 3"1/2 SCH 10S | 101,6x3,05  | 7,40  |
| 3"1/2 SCH 40S | 101,6x5,74  | 13,56 |
| 3"1/2 SCH 80S | 101,6x8,08  | 18,61 |
| 4 SCH 10S     | 114.3x3.05  | 8,50  |
| 4 SCH 40S     | 114.3x6.02  | 16,32 |
| 4 SCH 80S     | 114.3x8.56  | 22,67 |
| 5 SCH 10S     | 141,3x3,40  | 11,82 |
| 5 SCH 40S     | 141,3x6,55  | 22,20 |
| 5 SCH 80S     | 141,3x9,53  | 31,59 |
| 6 SCH 10S     | 168.3x3.4   | 14,04 |
| 6 SCH 40S     | 168.3x7.11  | 28,70 |
| 6 SCH 80S     | 168.3x10.97 | 43,22 |
| 8 SCH 10S     | 219.1x3.76  | 20,27 |
| 8 SCH 40S     | 219.1x8.18  | 43,39 |
| 8 SCH 80S     | 219.1x12.7  | 65,64 |